

Infrared group urinal flush valve with electric ALS SLP 05KX





Characteristics



- includes Bluetooth control
(paid Sanela control app available for download)
- is designed for flushing a group of urinals at once
- responds to the presence of people in front of the urinals in the axis of the sensor (approx. 200 mm from the front edge of the urinal) for longer than 7.5 s
- sensor range to the reflective foil up to 3 m (option to extend the range on request)
- all urinals will be flushed after all persons have left the monitored zone
- flush time is adjustable from 0.5 to 15.5 s
- parameter settings and communication with the electronics via Sanela control app (Bluetooth) or the SLD 03
- automatic flushing 24 hours after the last valve activation
- brushed finish

Building preparation



- 1 - power supply
- 2 - stainless steel cover with electronics
- 3 - installation box (stainless steel)
- 4 - installation box (plastic)
- 5 - reflective foil
- 6 - urinal
- 7 - connection of electronics and valve

Technical Specification

Stainless steel cover dimensions	170 x 170 x 10 mm
Dimensions	
▪ plastic box	140 x 140 x 75 mm
▪ stainless steel box with valve	145 x 155 x 100 mm
Supply voltage	24 V DC
Power input	7 W
Range	0,3 - 3 m
Recommended working pressure	0.15 - 0.6 MPa
Flow rate	70 l/min at pressure 0.15 MPa (informative value)
Water inlet	cross-section min. 32 mm (PN 16) external thread min. G 1"
Water outlet	external thread G 1"

Supply Specification

SLP 05KX - Supply No. 01055	stainless steel cover with electronics including Bluetooth module, plastic installation box with electronics, stainless steel installation box with fittings and solenoid valve, stainless steel cover (for covering the box with valve), reflective foil
------------------------------------	---

Recommended accessories

SLZ 01Y - Supply No. 05012	power supply 24 V DC for max. 5 flushers
SLZ 01Z - Supply No. 05011	power supply 24 V DC for max. 9 flushers
SLZ 04Y - Supply No. 05042	power supply 24 V DC for DIN rail, for max. 5 flushers
SLZ 04Z - Supply No. 05041	power supply 24 V DC for DIN rail, for max. 9 flushers
SLZ 04X - Supply No. 10049	power supply 24 V DC for DIN rail, for max. 15 flushers
SLZ 06 - Supply No. 05060	power supply 24 V DC for max. 1 flusher
SLD 03 - Supply No. 07030	remote control for an adjustment of parameters
SLA 02 - Supply No. 06020	inlet fitting with gasket for water supply to urinals with rear inlet
SLA 30 - Supply No. 06300	reflective foil
SANELA CONTROL APP	paid Sanela Control app available for download on the App Store and Google Play